

# इंटरनेट

# मानक

## Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 5000-OD38 (1984): Dimensions of Semiconductor Devices,  
Device Outline OD38 [LITD 5: Semiconductor and Other  
Electronic Components and Devices]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”



BLANK PAGE




Indian Standard



DIMENSIONS OF SEMICONDUCTOR DEVICES  
DEVICE OUTLINE OD 38

1. Dimensions — This drawing has been prepared in accordance with IS : 5001 ( Part 1 )-1969 'Guide for preparation of drawings of semiconductor devices and integrated circuits : Part 1 Semiconductor devices'.



Reference	Millimetres			Notes
	Min	Nom	Max	
D	—	—	42.0	—
D <sub>1</sub>	—	—	—	1,2
E	—	36	—	—
F	5.0	—	—	—
J	—	—	110	1,3
M	—	—	—	4
M <sub>1</sub>	20.0	—	27.0	5
N <sub>1</sub>	—	—	4.0	—
O	180	—	220	—
T	10.0	—	11.0	—
W	—	M20×1.5	—	—
Z	11.0	—	—	6
Type A				
N	23.0	—	25.0	—
Type B				
N	12.0	—	14.0	—

Adopted 5 January 1984

© December 1984, ISI

Gr 1

- Note 1** — The device, with the exception of the hexagon, thread and flexible terminal, lies within the cylinder of diameter  $D_1$  and length  $J$ .
- Note 2** — Diameter  $D_1$  shall not be greater than the actual across flats dimension of the hexagon used.
- Note 3** — Dimension  $J$  is the seated height with the terminal bent at right angles.
- Note 4** — Diameter  $M$  refers to zone  $N_1$ . The maximum value should not exceed the outside diameter of the thread.
- Note 5** — The contour and orientation of the terminal slug or lug are undefined.
- Note 6** — Minimum flat.

**2. Rules for Coding — See 8.1 of IS : 5001 ( Part 1 ) - 1969.**

**3. Equivalent Designations**

Country or Organisation	Designation Code	
	Type A	Type B
IEC	A35MA	A35MB
Germany	108B2	—
Japan	SC-30 △	—
USSR	—	KD8P1 △